



"KUFNER HAUTE COUTURE"

B961N90

Description:

An extremely fine, elastic woven interlining that redefines the boundaries of "softness". This ultra-light woven fusible has the world's finest double dot coating (30 mesh) guaranteeing a superb "soft-bond". The fineness of this new product creates a nearly invisible interlining that blends perfectly with ever the most shear fabrics. The latest addition to the KUFNER Haute Couture range.

Basic Composition 100 % PAF

Warp: Polyamid

Weft: Polyamid

Structure: Plain Weave

Total Weight: ca. 22 g/m²

Coating: PA-Double Spot; 30 Mesh (147 Dots/cm²) Random

Width: 090 cm

Colours: Colour range!

Application: DRY CLEANING (P)/WASHABLE at 40°C Code ISO 3758: 30240



Fusing Conditions

(Recommendation): **Glueline Temperature** 116°C - 121 °C

Fusing Time: 8 sec.

Press Power: 1,5 N/cm² (150 p/cm²) Flat Press

6 N/cm² (0,6 kp/cm²) Continuous Press

General Conditions of Guarantee: In view of the wide variety of existing fabrics and other materials used by the clothing industry, KUFNER INTERNATIONAL recommends that before industrial use complete tests are carried out with the fabrics and other materials to be used, and on the machines that will be used. The KUFNER INTERNATIONAL guarantee is explicitly limited to the replacement of any of its products recognized to be defective, to the exclusion of all other compensation or damages.